

## ST-625 THERMOPTEK SMOKE ALARM

<b>Sensor type</b>	Thermoptek Multi-Sensor
<b>Battery type</b>	2 x 1.5v AA alkaline batteries



- Thermoptek Multi-Sensor technology as used by over 90% of the UK Fire and Rescue Services.
- Large central button - test / Smart Silence.
- Easy to install with automatic battery engagement on base plate.
- Smart Silence - allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound.
- Sleep Easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.



## Technical Specification

<b>Dimensions</b>	107mm (diameter) x 34mm (depth)	
<b>Supply voltage</b>	3VDC	
<b>Battery</b>	x2 AA	
<b>Technology</b>	Thermoptek	
<b>Alarm sound level</b>	85dB(A) at 3m (minimum)	
<b>Installation positions</b>	Ceiling / Wall	
<b>Operating temperature</b>	+4°C to +38°C	
<b>Operating humidity</b>	Up to 90% RH non-condensing	
<b>Storage temperature</b>	-20°C to +60°C	
<b>Storage humidity</b>	Up to 93% RH non-condensing	
<b>Plastic material</b>	ABS, UL94 VO fire retardant	
<b>Warranty</b>	5 years	
<b>Weight</b>	157g	
<b>Certified to</b>	BSEN 14604:2005	
<b>Independently tested to</b>	N/A	
<b>Maximum number of connected units</b>	N/A	
<b>Operating frequency</b>	N/A	
<b>Range</b>	N/A	

For further information or sales enquires: [www.fireangel.eu](http://www.fireangel.eu)

GN4626R1