

HT-230 MAINS POWERED HEAT ALARM

Sensor type	Thermistek
Battery type	10 year sealed for life Panasonic lithium



- 10 year lithium battery back-up - no need to worry about changing the battery
- Hardwire interlink with up to 30 other FireAngel Pro alarms
- Modern design
- Combined central button - Test / Smart Silence / Locate
- Ultra slim, integrated mounting base for easy installation
- Intelligent locate feature - silence all but the initiating alarm on a network
- For use in kitchens, garages, lofts and other areas not suitable for a smoke alarm

Technical Specification

Dimensions	90mm (width) x 90mm (height) x 22.5mm (depth)
Supply Voltage	230V AC, 50Hz
Battery back-up	10 year sealed for life lithium battery
Technology	Class A1 heat sensor
Installation positions	Ceiling
Maximum number of connected units	30 hardwire interconnected
Alarms at temperature range	54°C to 65°C
Alarm sound level	85dB (A) at 3m (minimum)
Plastic material	ABS, (UL94 V0 flame retardant)
Approvals	BS 5446-2: 2003
Normal operating temperature	+4°C to +38°C
Normal operating humidity	Up to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	Up to 93% RH non-condensing
Weight	282g