

ST-750 THERMOPTEK® SMOKE ALARM

| | |
|---------------------|---------------------------------|
| Sensor type | Thermoptek Multi-Sensor |
| Battery type | 10 year sealed for life lithium |



- Thermoptek Multi-Sensor technology as used by over 90% of the UK Fire and Rescue Services.
- 10 year sealed for life **Panasonic** battery, removes the need to replace the battery.
- Large central button - Test / Smart Silence.
- Easy to install with automatic battery engagement on base plate.
- Smart Silence - allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound.
- Sleep Easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.



Technical Specification

| | | |
|-------------------------------|--|--|
| Dimensions | 130mm (diameter) x 34mm (depth) | |
| Supply voltage | 3V DC | |
| Battery | 10 year sealed for life Panasonic battery | |
| Technology | Thermoptek | |
| Alarm sound level | 85dB(A) at 3m (minimum) | |
| Installation positions | Ceiling / Wall | |
| Operating temperature | +4°C to +38°C | |
| Operating humidity | Up to 90% RH non-condensing | |
| Storage temperature | -20°C to +60°C | |
| Storage humidity | Up to 93% RH non-condensing | |
| Plastic material | ABS, UL94 VO fire retardant | |
| Warranty | 10 years | |
| Weight | 155g | |
| Certified to | BS EN 14604:2005 +AC:2008 | |
| Barcode | 0816317004064 | |