

Spec+

FireAngel

Multi-Sensor Heat and CO Alarm

QUICK REFERENCE CODE

SP530

PRODUCT CODE


FA4451BW

Features Overview

- Thermistek™ enhanced sensing - High performance thermistor and predictive monitoring ensure a quicker response to fires.
- Bluetooth (BLE) on board, no need for additional modules. Low power consumption, data encryption and high reliability.
- Low battery warning.
- Extract and share product status and data reporting via the Angel Pro app.
- Class A1 heat detection with hidden heat cap.
- Sleep Easy™ - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.
- Night Sensing - senses ambient light and reduces the brightness of the green power LED to prevent sleep disturbance.
- End of Life Indication - a clear reminder to replace the alarm.
- 10 year rechargeable back-up lithium battery.



Technical Specification

Dimensions	W148 X D45mm	
Supply voltage	AC 230V / 50Hz	
Battery	Mains powered with 10 year rechargeable lithium battery back-up - Panasonic	
Sensor technology	Electrochemical & Thermistek™ technology (Class A1 detection)	
Alarm sound level	>85 dB at 3m	
Installation positions	Ceiling / Wall	
Operating temperature	-10°C (14°F) to +40°C (104°F)	
Operating humidity	10% - 95% RH (non condensing)	
Storage temperature	-20°C (-4°F) to +55°C (131°F)	
Storage humidity	10% to 95% RH (non condensing)	
Warranty	10 Years	
Certified to	BS 5446-2:2003. EN 50291-1:2018. SGS PT/25/GEN/0730	
Weight	312g	
Plastic material	PC/ABS	
Maximum number of connected devices	50 Devices (wired and wireless)	
Wireless range	≤35m (>120m in clear air)	
Wireless protocol/freq	BLE 2.4GHz	



SP500
Smoke



SP510
Heat



SP520
Smoke & Heat



SP540
Smoke, Heat & CO

