

Spec+ Hard-Wired Controller

FireAngel

QUICK REFERENCE CODE

SP565

PRODUCT CODE

FA4564-T

Features Overview

- 10-year product life.
- Mains powered.
- Wall-mounted installation, supplied with surface mounting box and compatible with standard UK 1-gang back boxes.
- Three dedicated switches for test, silence and locate.
- Hard-wired interlink with up to 50 compatible FireAngel Spec+ alarms and accessories.
- Centralised test, silence and locate functions for interlinked alarms.
- When one alarm sounds, all interlinked alarms sound for property-wide warning.



Technical Specification



Dimensions	W87mm x H87mm x D43mm	
Supply voltage	AC 230V/ 50hz	
Installation positions	Wall/Embedded in the wall	
Operating temperature	-10°C to 40°C	
Operating humidity	15 - 95% RH (non-condensing)	
Storage temperature	-10°C to 40°C	
Storage humidity	15% to 95% RH (non condensing)	
Warranty	5 Year	
Certified to	EN 55032:2015+A11:2020+A1:2020, EN 61000-3-3:2013 +A1:2019 +A2:2021 EN IEC 61000-3-2:2019 +A1:2021 +A2:2024, EN 55035:2017+A11:2020 IEC 62368-1:2023 , EN IEC 62368-1:2024+A11:2024	
Weight	200±5g	
Plastic material	Bakelite, UL94 VO fire retardant	
Maximum number of connected devices	50 Hardwired devices	
IP Rating	IP20	

Related Products



SP500
Smoke



SP510
Heat



SP520
Smoke & Heat



SP530
Heat & CO



SP540
Smoke, Heat & CO

