

FA8080BW

Wireless Gateway

FireAngel ^{one}


Features Overview

- Four programmeable action buttons, controlled via the app.
- Powered using a standard USB-C cable.
- As the hub of smart home, by integrating the FireAngel platform and APP, it can connect to BLE Mesh sub-devices to achieve remote monitoring and management.
- It can also be directly connected via mobile phone Bluetooth to achieve local debugging and control.
- It can be flexibly wall-mounted or desktop installed to meet the needs of different scenarios.
- It is simultaneously compatible with mainstream smart speakers from Google, Apple, Amazon, etc., easily integrating into the smart ecosystem.



Technical Specification




Dimensions	70mmX70mm (diameter) x 21mm (depth)	
Supply voltage	DC 5V (USB Type-C)	
Standby consumption	<5W	
WIFI frequency	2.4G: 2412~2484MHz 5G: 5180~5885MHz	
Bluetooth	Bluetooth 5	
Wireless protocol	Bluetooth Mesh, WIFI 6	
Product Life	10 Years	
Operating humidity	≤95% RH (non condensing)	
Operating temperature	-10°C to +50°C (14°F to 122°F)	
Storage humidity	Up to 95% RH (non condensing)	
Warranty	5 Years	
Independently tested to	EN 301 489-1, EN 301 489-3, EN 301 489-17, EN 300 328, EN 300 440, EN 301 893.	
Weight	52g	

Recommended Additional Products

Connect up to 20 compatible devices

This wireless gateway links your smoke, heat, and carbon monoxide alarms to create a smarter, safer network.



FA8620BW
BLE Smoke Alarm



FA8720BW
BLE Heat Alarm



FA8922BW
BLE Smoke & Heat Alarm

