FA8620BW

Optical Smoke Alarm
Wireless Interlink

FireAngel one

Features Overview


- Smart network - connect up to 20 devices via Bluetooth wireless interlink.
- Eco friendly plastics - made using more than 50% recycled plastics.
- Sealed for life battery for up to 10 years protection.
- Sleep easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.
- End of life indication - a clear reminder to replace the alarm after 10 years, which can be silenced.
- Suitable for installation in the landing, hallway, bedrooms, lounge and dining rooms.
- 5 year warranty.



Technical Specification

CE 26 2531
EN 14604:2005+AC:2008
Smoke alarm devices
FSTDOP26004

Global Recycled Standard
>50% Recycled Plastics
Certified By TUV No:
TRC-GRS-222329-00

Dimensions	118mm (diameter) x 37.5mm (depth) 
Supply voltage	3V DC
Battery	10 year sealed for life battery
Product life	10 Years - Replace unit after 10 years of operation
Sensor technology	Optical (UltraSense™)
Alarm sound level	≥85dB at 3m
Installation positions	Ceiling / Wall
Operating temperature	-10°C to 40°C (14°F to 104°F)
Operating humidity	<93% relative humidity (non-condensing)
Storage temperature	-20°C to 55°C (-4°F to 131°F)
Storage humidity	<93%RH (non-condensing)
Warranty	5 Years
Certified to	EN14604:2005 +AC:2008
Weight	151g
Wireless Protocol	Bluetooth - 2.4GHz
Maximum Interlink Distance	35m (>100m in clear air)

More interlink products from this range...



FA8720BW
Wireless interlink heat alarm



FA8922BW
Wireless interlink smoke & heat alarm



FA8827BW
Wireless interlink CO alarm



FA8080BW
Wireless gateway