

FA8620BW

Optical BLE Smoke Alarm

Wireless Interlink

FireAngel 

Features Overview

- Smart network - connect up to 20 devices via Bluetooth wireless interlink.
- Eco friendly plastics - made using more than 50% recycled plastics.
- Tamper proof - sealed for life battery for up to 10 years protection.
- Sleep easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.
- End of life indication - a clear reminder to replace the alarm after 10 years, which can be silenced.
- Suitable for installation in the landing, hallway, bedrooms, lounge and dining rooms.
- 5 year warranty.




Technical Specification



2531
EN 14604:2005+AC:2008
Smoke alarm devices
FSTDOP26004



Dimensions	118mm (diameter) x 37.5mm (depth)	
Supply voltage	3V DC	
Battery	10 year sealed for life battery	
Sensor life	10 Years - Replace unit after 10 years of operation	
Sensor technology	Optical UltraSense™	
Alarm sound level	≥85dB at 3m	
Installation positions	Ceiling / Wall	
Operating temperature	-10°C to 40°C (14°F to 104°F)	
Operating humidity	<93% relative humidity (non-condensing)	
Storage temperature	-20 to 55°C (-4°F to 131°F)	
Storage humidity	<93%RH (non-condensing)	
Warranty	5 Years	
Certified to	EN14604:2005 +AC:2008	
Weight	155±5g	
Wireless Protocol	Bluetooth - 2.4GHz	
Maximum Interlink Distance	20m (<150m in clear air)	

More products from this range...



FA8615BD
Wireless diagnostic
smoke alarm



FA8720BW
Wireless interlink
heat alarm



FA8922BW
Wireless interlink
smoke & heat alarm



FA8827BW
Wireless interlink
CO alarm



FA4557BW
Wireless
gateway

