FA8922BW

Smoke & Heat Alarm
Wireless Interlink

FireAngel one

Features Overview


- Smart network - connect up to 20 devices via Bluetooth wireless interlink.
- Eco friendly plastics - made using more than 50% recycled plastics.
- Sealed for life battery for up to 10 years protection.
- Sleep easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.
- End of life indication - a clear reminder to replace the alarm after 10 years, which can be silenced.
- Suitable for installation in the kitchen, garage, loft and utility room.
- 5 year warranty.



Technical Specification

CE 26 2531
EN 14604:2005+AC:2008
Smoke alarm devices
FSTDOP26005

Global Recycled Standard
>50% Recycled Plastics
Certified By TUV No:
TRC-GRS-222329-00

Dimensions	118mm (width) x 49mm (depth) 
Supply voltage	3V DC
Battery	10 Year sealed for life lithium battery
Product life	10 Years - Replace unit after 10 years of operation
Sensor technology	Smoke: Optical (UltraSense ™) Heat: Thermistor (Class A1 Detection)
Alarm sound level	≥85dB at 3m
Installation positions	Ceiling / Wall
Operating temperature	-10°C to 40°C
Operating humidity	<93% relative humidity (non-condensing)
Storage temperature	-20°C to 55°C (-4°F to 131°F)
Storage humidity	<93%RH (non-condensing)
Warranty	5 years
Certified to	EN 14604:2005/AC:2008, BS 5446-2:2003, RED 2014/53/EU
Weight	156g
Wireless Protocol	Bluetooth - 2,4GHz
Maximum Interlink Distance	15m (>80m in clear air)

More interlink products from this range...



FA8620BW
Wireless interlink smoke alarm



FA8720BW
Wireless interlink heat alarm



FA8827BW
Wireless interlink CO alarm



FA8080BW
Wireless gateway