

FA8922BW

Smoke and Heat Alarm

Wireless Interlink

FireAngel 

Features Overview

- Smart network - connect up to 20 devices via Bluetooth wireless interlink.
- Eco friendly plastics - made using more than 50% recycled plastics.
- Tamper proof - sealed for life battery for up to 10 years protection.
- Sleep easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.
- End of life indication - a clear reminder to replace the alarm after 10 years, which can be silenced.
- Suitable for installation in the landing, hallway, bedrooms, lounge, kitchen and dining rooms.
- 5 year warranty.




Technical Specification



2531
EN 14604:2005+AC:2008
Smoke alarm devices
FSTDOP26005



Dimensions	118mm (diameter) x 49mm (depth)	
Supply voltage	3V DC	
Battery	10 Year sealed for life lithium battery	
Sensor type	Smoke sensor: Optical UltraSense™ Heat Sensor: Thermistor (Class A1 detection)	
Alarm sound level	≥85dB at 3m	
Installation positions	Ceiling / Wall	
Operating temperature	-10°C to 40°C	
Operating humidity	<93% relative humidity (non-condensing)	
Storage temperature	-20°C to 55°C (-4°F to 131°F)	
Storage humidity	<93%RH (non-condensing)	
Warranty	5 Years	
Certified to	EN 14604:2005/AC:2008, BS 5446-2:2003, RED 2014/53/EU	
Weight	158±5g	
Wireless Protocol	Bluetooth - 2.4GHz	
Wireless Distance	20m (<150m in clear air)	

More products from this range...



FA8615BD
Wireless diagnostic
smoke alarm



FA8620BW
Wireless interlink
smoke alarm



FA8720BW
Wireless interlink
heat alarm



FA8827BW
Wireless interlink
CO alarm



FA4557BW
Wireless
gateway

